# Monthly PMP Checklist For Service Provider

Date:	: Store Locatio	n: Store #
Com	pleted by:	
•		
	Before performing any maintenance	perform proper lock-out / tag-out procedure!
Check		position proper soon carry and careprocessaries
Off		
Perfo	orm Daily Inspection	
	Using the checklist, inspect the me	chanical room & tunnel, then run a test car
High-	-Pressure Pump Station	
	Check belts for visible signs of wea	ır
	Verify pump oil is dark green, not m	nilky or black & is at correct level
	Verify correct operating pressure (8	300 psi)
	Check tank for sediment or debris	
	Listen for chatter or cavatation fron	n pump
	•	
Floor	r Heat Boiler	
(If app	olicable in cold weather)	
	,	d appropiate antifreeze level in sight-glass
		3 3 3
Moto	or & Control Center	
	Check all air regulators for proper s	settings
	Inspect chemical delivery systems	
	mopost shormest delivery systems	or round and propor operation
Chen	mical Delivery & Rinse Arches	
	Unclog nozzles and adjust foamers	s as needed
	Check condition of hoses and conn	
	eriosix certaineri er riecce aria certi	iodiono
Chen	mical Wheel Applicators	
Onon	Check pattern of spray	
	Check coverage on wheels	
	Tolleck coverage off wheels	
Entra	ance Photo Eyes	
Liitia		
	Gently wipe eyes clean	on unit)
	Check for proper alignment (lights	on unit)
Ton [	Dwine	
тор в	Brush	
	Check wash material for wear	
	Grease brush core & 2 pivot arm be	
	Check for loose fasteners or rod er	IOS
	Check for worn bearings	
	Lubricate retract cylinder with Tri-flo	
	Check air pressure regulator setting	
	Check for loose fasteners or rod er	ids
	Check for wear on bearings	
	Lubricate retract cylinder with Tri-Fl	
1	Ensure movement is smooth during	r extend & retract

## **High-Pressure Wheel Blaster**

Check condition of hoses		Check condition of hoses
		Rotate nozzle body to prolong wear
		Check for loose fasteners or rod ends
		Clean filters and debris from nozzles if necessary

## **Triple Foamer**

Check for proper foam application

## **RS-701 SuperFlex Wrap**

Check wash material for wear	
	Grease 2 bearings on main arm and 1 on secondary arm (each side)
	Check for loose fasteners or rod ends
	Check for wear on bearings
Grease rod end bearings 4 on each arm	
Check oil reservoir (fill if needed)	
	Check wrap-around for proper operation

#### Conveyor

(Remember to lockout power before servicing)

Check roller up gate for free movement	
Check chain tension make necessary adjustments or remove links if necessary	
Check condition of air tension cylinders and listen for air leaks	
Grease all Zerk fittings at entrance and exit	
Lubricate roller up gate cylinder with Tri-Flo	
Check tension cylinders for wear, lubricate with Tri-Flo	
Inspect and clean clock switch make necessary adjustments	
Inspect gear box shaft for oil leaks	
Inspect conveyor weldments	
Make sure grates are in place and flat. Bent grates can cause personal injury or vehicle damage.	
Make sure chain is making proper contact with sprocket	
Check sprocket for excess wear	
Check bearings on take up drum for slop	
Check fasteners on safety mat	
Put all rollers on top deck and inspect for loose assemblies	
Check trench for water backing up and that drain is clear	

#### **Blowers**

Visually inspect impellers through intake and outlet.
Visually inspect smart nozzle for proper movement
Check belt on smart nozzle for wear
Inspect all mounting hardware

## **Prep Gun**

Check to make sure protective tip is on and in good condition
Check for leaks
Check spray pattern
Hold gun in on position feel for strong steady delivery with no pulsation

## **Air Compressor**

Drain water from tank
Check site glass to ensure oil is not milky or black

#### **Hydrominders**

ĺ	Check for smooth operation of flo	at
ĺ	Check tank and inlet screen for de	ebris, clean if necessary.

#### **Overhead Doors**

Inspect overall condition	
Lubricate rollers, hinges & locks	
Check for proper operation of saf	ety eyes and inductive loops

### Water Conditioning Equipment

- 4	9 1 1
	Test water for Hardness and TDS
	Check salt level in brine tank and fill with site salt if needed

## Reclaim System

riociann e yetem	
Follow maintenance procedures,	clean strainer basket, check filter on oxygen concentrator
Check input and output pressures	s, if different by 15 psi then clean filter following instructions

#### **NOTE ANY PROBLEMS BELOW:**

Review findings with site manager. Discuss action plan note below and get signature.

Do not make any repairs or adjustments unless properly trained & qualified!